

# INSTRUCTIONS FOR SPEED RING 2270/2270AL

Fits Norman LH2400 and LH500 flash heads

## Mounting the Ring to the light:

- 1- Remove the large thumbscrew and reflector clip from the top of the Norman head.
- 2- Unscrew the umbrella slot-tightening knob so it clears the inside dimension of the hole.
- 3- Slide the Speed Ring over the Norman head from the front with the flat mounting bracket (A) aligned over the top of the housing, then insert the bottom bracket (B) into the umbrella holder and tighten the knob.
- 4- Insert the supplied ¼-20 x ½" thumbscrew through the top bracket and tighten to the top of the housing.

## Parts List for 2270:

1	20801000	6.2" Speed Ring
1	22502000	Norman 2000 insert
1	22703000	Top mounting bar
1	22704000	Bottom mounting bar
1	26105100	¼-20 x ½" t-screw
10	20305100	10-24 x 3/8" Nylock screw
8	20307000	#10 washer S/SS
8	20408000	Nylon washer

## Parts list for 2270AL:

1	24051000	Metal Speed Ring
1	22502000	Norman 2000 insert
1	22703000	Top mounting bar
1	22704000	Bottom mounting bar
1	26105100	¼-20 x ½" t-screw
10	20305100	10-24 x 3/8" Nylock screw
8	20307000	#10 washer S/SS
16	24058100	#10 teflon washer .031
8	24058300	Teflon D washer .093

